

DECLARATION OF PERFORMANCE NO 08CE/BIb/CSE/04

- 1. The unique identification code of the product type: 08/Blb/GL/CSE
- 2. Intended use or use:

Dry-pressed ceramic tiles with water absorption equal to 0.5%< $E_b \le 3\%$; Annex H; BIb group, glazed (GL), clinker; for interior and exterior walls and floors of buildings - as described on the packaging.

- 3. Manufacturer: CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce
- 4. System(s) of assessment and verification of constancy of performance: SYSTEM 4
- 5. Harmonised standard: EN 14411:2012
- 6. Declared performance:

Essential characteristics	Performance (level and/or class)	Harmonised technical specification
Reaction-to-fire performance	A1 _{FL}	Classified Without Testing (CWT)
Release of dangerous substances:		
- Cadmium	Max 0,07mg/mm ²	
- Lead	Max 0,8mg/mm ²	
Breaking strength:		1
- thickness ≥7,5mm	≥ 1100N	
- thickness <7,5mm	≥ 700N	
Bond strength/adhesion [N/mm2]:]
- cementitious adhesives		EN 14411:2012
- dispersion adhesives	NPD - No Performance Determined	
- reaction resin adhesives		
- mortar		
Slippage according to CEN/TS 16165:2012, Annex B	According to the packaging	
Thermal shock resistance	Meets	
Durability for:		1
- internal use:	Meets	
- external use: resistance to freeze-thaw cycles	Meets	
Tactility	NPD - No Performance Determined	

A copy of the Declaration of Performance is available on the website: www.cersanit.com

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Signed on behalf of the manufacturer:

QUALITY SYSTEM MANAGER
Jolanta Grzebna
0
(signature)

Kielce, 01.06.2017 (place and date of issue)