DECLARATION OF PERFORMANCE NO 03CPR/BIa/RO/03

1. The unique identification code of the product type: **03/BIa/GL/RO**
2. Intended use or use:

   Dry-pressed ceramic tiles with low water absorption E≤0.5%; Annex G; Bla group, glazed (GL) Gres Porcellanato; for interior and exterior walls and floors of buildings - as described on the packaging.
3. Manufacturer: **ROVESE S.A.; AL. Solidarności 36; 25-323 Kielce**
4. System(s) of assessment and verification of constancy of performance: ***SYSTEM 4***
5. Harmonised standard: **EN 14411:2012**
6. Declared performance:

Essential characteristics	***Performance (level and/or class)***	***Harmonised technical specification***
Reaction-to-fire performance	$A1_{FL}$	*Classified Without Testing (CWT)*
Release of dangerous substances:		EN 14411:2012
- Cadmium	Max 0,07mg/mm^2	
- Lead	Max 0,8mg/mm^2	
Breaking strength:		
- thickness ≥7,5mm	≥ 1300N	
- thickness <7,5mm	≥ 700N	
Bond strength/adhesion [N/mm2]:		
- cementitious adhesives	*NPD - No Performance Determined*	
- dispersion adhesives		
- reaction resin adhesives		
- mortar		
Slippage according to DIN 51130	*According to the packaging*	
Thermal shock resistance	*Meets*	
Durability for:		
- internal use:	*Meets*	
- external use: resistance to freeze-thaw cycles	*Meets*	
Tactility	*NPD - No Performance Determined*	

A copy of the Declaration of Performance is available on the website: www.rovese.com

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Signed on behalf of the manufacturer:

Kielce, 01.01.2017
(place and date of issue)

.....
(signature)